ORIGINAL

EX PARTE OR LATE FILED



Federal Communications Commission Washington, D.C. 20554

April 8, 2002

RECEIVED

APR - 8 2002

PERSONAL COMMUNICATIONS COMMUNICATION
GPYCE OF THE SECRETARY

William F. Caton
Acting Secretary
Office of the Secretary
Federal Communications Commission
445 12th Street, S.W., Room TW-B204
Washington, D.C. 20554

Re:

Ex Parte Meeting – Application by Verizon New England Inc. for Authorization to Provide In-Region, InterLATA Service in the State of Vermont (Docket No. 02-7)

Dear Mr. Caton:

The Pricing Policy Division (PPD) of the Wireline Competition Bureau of the Federal Communication Commission (Commission) hereby provides notice of an *ex parte* meeting held on April 3, 2002 with representatives of Telcordia Technologies (Telcordia). The meeting was held in response to a request from PPD staff, and Telcordia is not a party to this proceeding. PPD therefore files this notice of the meeting pursuant to the Commission's *ex parte* rules. *See* 47 C.F.R. §§ 1.1204(a)(10)(iii), 1.1206(b).

The following PPD staff members attended the meeting: Tamara Preiss, Deena Shetler, Aaron Goldschmidt, Josh Swift, Nese Guendelsberger, Monica Desai, Victoria Schlesinger, Douglas Galbi, Raj Kannan, Steve Morris, Richard Kwiatkowski, and Carol Canteen. The following Telcordia representatives attended the meeting: Louise Tucker, David Garfield, and Wilfred McKoy.

During the meeting, Telcordia representatives explained busy hour engineering in the context of the Switching Cost Information System (SCIS) model. Telcordia representatives also discussed busy hour to any time, any day cost calculation. The attached written materials accurately summarize Telcordia's presentation.

Deena Shetler

Sincerely,

Deputy Chief, Pricing Policy Division

No. of Copies rec'd. List ABCDE

Wireline Competition Bureau

We determine that it is in the public interest to publish notice of this ex parte meeting. See 47 C.F.R. § 1.1200(a)

Attachments

Qualex International, Inc. Susan Pie, Room 5-C224 cc:





Performance from Experience

Representative Calculations

David Garfield 732-699-2482 dgarfiel@telcordia.com April 3, 2002

"Busy Hour" Switching System Traffic

- Provide Best Possible Service At The Least Possible Cost
- Switching equipment provided to accommodate "peak" load that occurs in a specific time period (Busy Hour)
 - Include frequent peaks (i. e., normal business days)
 - Exclude infrequent peaks (Mother's day, snow storms, etc.)
- "Busy Hour" Determined From Special Traffic Study
 - Traffic measured every hour every day
 - Data from weekends & holidays excluded
 - "Busy Hour" determined from remaining data
- Traffic Measured Only In "Busy Hour" Thereafter
 - Traffic measured every business day throughout the year



"Busy Hour" Switching System Traffic

Month	Day	BH Traffic (Minutes)	BH Minutes Per Line	CCS Per Line
January	Day 1	50,000	5	3.0 (5 * 60) / 100
	Day 2	43,000	4.3	2.58 (4.3 * 60) / 100
	Day 3	47,500	4.75	2.85 (4.75 * 60) / 100
			• • •	
•••		•••	•••	•••
•••			•••	• • •
December			•••	• • •
	Day 363	52,000	5.2	3.12 (5.2 * 60) / 100
	Day 364	49,800	4.98	2.99 (4.98 * 60) / 100
	Day 365	40,300	4.03	2.42 (4.03 * 60) / 100






- High Day Busy Hour (HDBH)
 - Maximum (Day 1, Day 2, ..., Day 365)
 - Exclude weekends & holidays
- Average Busy Season Busy Hour (ABSBH)
 - Determine total traffic by month, excluding weekends & holidays
 - Determine 3 busiest months of the year

Busy Month 1 + Busy Month 2 + Busy Month 3

- ~ 60 Days (90 Days Less Weekends & Holidays)
- Time Consistent Busy Hour (TCBH)
 - Same busy hour assumed each day
 - Data measured in the same hour each day
- Bouncing Busy Hour (BBH)
 - Busy hour can be different each day
 - Data measured in true busy hour each day
 - _{la.} Used as the basis for Extreme Value Engineering (EVE)



Lucent's 5ESS Access Interface Unit (AIU) - Architecture



Application Pack

- 32 analog lines per analog line pack
- Provides BORSCHT

AIU

- 20 slots for application packs
- 4 ring generators required for power ringing
 - Consumes 4 application pack slots
 - Common resource for 3 AIUs
 - 2 of 3 AIUs have 640 line capacity (20 * 32)
 - 1 of 3 AIUs have 512 line capacity (16 * 32)
- Concentration ratio based on PIDBs per AIU



Performance from Experience

SCIS/MO Input Data - Analog Lines Terminated On AIU

General		
Enter the ratio of High Day Busy Hour CGS to Average Busy Season Busy Hour CGS, not the call ratio. Range: 1.00 - 1.30	HD/ABS CCS Ratio	
Enter a single administrative fill factor applicable to all 2 wire POTS and BRI line terminations. Range: 0.01 - 100.	2 Wire Line Administrative Fill Factor	

	Lines & Trunks	
HL1PLines	Enter number of working POTS lines terminated on the Access Interface Unit (AIU). Range: 0 - 588800.	Number of AIU POTS lines
	Enter the ABSBH originating and terminating CCS per line for POTS lines terminated on the Access Interface Unit (AIU). Range: 0.01 -	ABSBH O+T CCS Per
L1PCCS	36. 4 1 1 2 1 2 1 2 1 2 2 2 2 2 2 2 2 2 2 2	Line for AIU POTS lines



PIDBs Per AIU Engineering

Table: AIU PIDB CCS Capacity Table

Generic: 5E15 Effective Date:

March 1, 2001

Item No.	Description	PIDBs	ABSBH CCS Capacity	HD CCS Capacity
	0 PIBDs Per AIU	0	0	0
2	2 PIDBs Per AIU	2	1843.2	2073.6
3	4 PIDBs Per AIU	4	3686.4	4147.2
4	6 PIDBs Per AIU	6	5875.2	6220.8
	8 PIDBs Per AIU	8	7833.6	8294.4

- Determine PIDBs per AIU based on:
 - 640 lines per AIU
 - 2.8 ABSBH O+T CCS per line
 - 1.2 High Day to Average Busy Season ratio

- Determine PIDBs per AIU based on:
 - 512 lines per AIU
 - 2.8 ABSBH O+T CCS per line
 - 1.2 High Day to Average Busy Season ratio



PIDBs Per AIU Engineering

Table: AIU PIDB CCS Capacity Table
Generic: 5E15

Effective Date: March 1, 2001

Item No.	Description	PIDBs	ABSBH CCS Capacity	HD CCS Capacity
1	0 PIBDs Per AIU	0	0	0
2	2 PIDBs Per AIU	2	1843.2	2073.6
	4 PIDBs Per AIU	4	3686.4	4147.2
4	6 PIDBs Per AIU	6	5875.2	6220.8
5	8 PIDBs Per AIU	8	7833.6	8294.4

640 Lines per AIU

- ABSBH CCS demand = 640 * 2.8
 = 1792
- ABSBH based PIDBs per AIU = 2
- HDBH CCS demand = 640 * 2.8 *
 1.2 = 2150.4
- HDBH based PIDBs per AIU = 4
- PIDBs per AIU₆₄₀ = Max(2,4) = 4
- ABSBH PIDB CCS capacity = 3686.4

512 Lines per AIU

- ABSBH CCS demand = 512 * 2.8
 = 1433.6
- ABSBH based PIDBs per AIU = 2
- HDBH CCS demand = 512 * 2.8 *
 1.2 = 1720.32
- HDBH based PIDBs per AIU = 2
- PIDBs per AIU₅₁₂ = Max(2,2) = 2
- ABSBH PIDB CCS capacity = 1843.2



Investment Per ABSBH Line (O+T) CCS

Final ABSBH CCS Capacity Per AIU

$$\frac{2*3686.4+1*1843.2}{3} = 3072.0$$

• Investment per Line (O + T) CCS (Part B) for analog lines on AIU:





Busy Hour to Any Time Any Day Cost Calculation

Wilfred A. McKoy

Director – Cost Models Practice 770-351-4069

Email: wmckoy@telcordia.com

Investment to Cost Calculation

Busy Hour/Total Day Ratio:

 The amount of traffic in the Busy Hour compared to the total amount of traffic carried over 24 hour period.

Equivalent Business Days Per Year:

- This number allows for resources to be recovered equally over all or a majority of days in the year.
- User would determine if the feature is a POTS or Business feature thus how many days are in the year.



Investment to Cost Calculation (Conversion of SCIS Investment Per BH CCS to BH Call)

Investment Per BH Call = SCIS/MO Investment Per BH CCS * HT Per Call

Example

\$50 * 6 = \$300 Per BH Call

Where:

\$50 = SCIS/MO Inv. Per BH CCS

6 = Holding Time Per Call in CCS (10 minute call = 600 seconds = 6 CCS)



Investment to Cost Calculation *(Example)*

Any Time Any Day Cost = Investment per BH Call * ACF * BHTD Ratio EBDY

\$300.00 * .30 *.10 /365 = \$.025 Cost per Call

where:

\$300.00 = Investment per BH Call

.30 = Annual Cost Factor (ACF)

10% = BHTD Ratio

365 = EBDY

